

If only everything in life
is as reliable as a Yanmar



YANMAR

Made in Japan

Yanmar EF352T 4WD
(35HP)



1933



1921



Yanmar EF453T 4WD
(45HP)

Strong, Comfortable and Fast...

Direct Fuel Injection Farm Tractors

If durability is on the top of your criteria list when choosing a farm tractor, then Yanmar is your final choice. Yanmar agriculture tractors are renowned world-wide for being the most reliable and fuel efficient tractors you will ever own. The new TNV series direct injection diesel engines fitted in Yanmar tractors will deliver the power you require for your agriculture needs whilst being kind to the environment.

100th
ANNIVERSARY



Palm Mach Sdn Bhd

www.palmmach.com

KUALA LUMPUR HEAD OFFICE

No. 3A, Jalan Perindustrian Desa Aman 1A, Industri Desa Aman, Kepong, 52200 Kuala Lumpur, Malaysia
Tel: (03) 6272.2439, 6272.6514 • Fax: (03) 6272.2461 • Email: info@palmmach.com



YANMAR

4WD Farm Tractors



Yanmar EF352T Specifications

Engine	Make	Yanmar		
	Model	3TNV88		
	Type	Direct Injection, water-cooled, diesel		
	Horsepower	hp	35	
	Rated RPM	rpm	2600	
	No of cylinder	3		
	Displacement	cc	1642	
	Fuel tank	litres	28	
Dimension	Overall length	mm	2850	
	Overall width	mm	1325	
	Overall height	mm	1960	
	Tread	Front	mm	1000
		Rear	mm	1105
	Wheel base	mm	1600	
	Ground Clearance	mm	350	
Weight		kg	920	
Drive System	4-wheel drive			
Tyre	Front	7.0 – 14		
	Rear	11.2 – 24		
Steering	Type	Hydrostatic power steering		
Brake	Type	Wet disc		
Clutch	Type	Dry single		
Transmission	Main shifting	Collar shift with Reverser		
	Gear shifting	8 Forward + 8 Reverse		
Roll Over Protection System	std	2-post foldable		
Travel	Travel	Forward	km/h	1.34–23.4
	Speed	Reverse	km/h	1.31–23.0
Hydraulic System	Turning Radius	mm	2200	
	PTO	rpm	540	
	Type	Position Control		
	Hitch	3-point hitch, SAE 1		
	Category	Category 1		
	Lifting Capacity	kg	1000	
	Hydraulic pump rate	l/m	23	

Yanmar EF453T Specifications

Engine	Make	Yanmar		
	Model	4TNV88		
	Type	Direct Injection, water-cooled, diesel		
	Horsepower	hp	45	
	Rated RPM	rpm	2700	
	No of cylinder	4		
	Displacement	cc	2189	
	Fuel tank	litres	40	
Dimension	Overall length	mm	3230	
	Overall width	mm	1605	
	Overall height	mm	2160	
	Tread	Front	mm	1292
		Rear	mm	1270 – 1830
	Wheel base	mm	1830	
	Ground Clearance	mm	375	
Weight		kg	1450	
Drive System	4-wheel drive			
Tyre	Front	8.0 – 16		
	Rear	12.4 – 28		
Steering	Type	Hydrostatic power steering		
Brake	Type	Wet disc		
Clutch	Type	Dry single		
Transmission	Main shifting	Collar shift with Reverser		
	Gear shifting	9 Forward + 9 Reverse		
Roll Over Protection System	std	2-post foldable		
Travel	Travel	Forward	km/h	1.57 – 27.8
	Speed	Reverse	km/h	1.62 – 28.6
Hydraulic System	Turning Radius	mm	2500	
	PTO	rpm	540	
	Type	Position Control		
	Hitch	3-point hitch, SAE 1		
	Category	Category 1		
	Lifting Capacity	kg	1350	
	Hydraulic pump rate	l/m	32.2	

All data subject to alteration without notice.



PALM MACH SDN BHD Branches

Kluang, Johor
No. 57, Jalan 2
Taman Sri Kluang
86000 Kluang, Johor
T/F: (07) 771.0419
E: service.kluang@palmmach.com

Kuching, Sarawak
Lot 2401
Batu Kitang Light Industrial Park
7½ Mile, Jalan Batu Kitang
93250 Kuching, Sarawak
T: (082) 628.896
F: (082) 628.897
E: sales.kch@palmmach.com
parts.kch@palmmach.com

Bintulu, Sarawak
Sublot 63, Lot 2370 & 2371
Sebiew Industrial Estate
Jalan Bintulu-Tatau
97000 Bintulu, Sarawak
T: (086) 330.282, 312.282
F: (086) 314.282
E: sales.bt@palmmach.com
parts.bt@palmmach.com

Kota Kinabalu, Sabah
Lot 12, House 21
Taman Tanah Emas
Off Jalan Penampang
88300 Kota Kinabalu, Sabah
T/F: (088) 260.100
E: service.kk@palmmach.com

Sandakan, Sabah
SEDCO Light Industrial
Lot No. 8, Lorong SEDCO 2
Mile 3, North Road
90000 Sandakan, Sabah
T: (089) 202.885, 203.885
F: (089) 201.362
E: sales.sdk@palmmach.com
parts.sdk@palmmach.com

Lahad Datu, Sabah
MDLD 4983, Lot 22
New Kimbell Light Industrial Estate
Mile 2 Jalan Dam
91100 Lahad Datu, Sabah
T: (089) 882.708, 882.885
F: (089) 881.362
E: sales.ld@palmmach.com
parts.ld@palmmach.com

Keningau, Sabah
33, Taman Golf View Keningau
89007 Keningau, Sabah
T: (014) 553.7836